


Professionally approved products.

Datasheet

**RS 4 pairs , 100m CW1308 Twisted Telecom
Cable White Sheath**

Stock Number - 520-2649



Description:

Rated Temperature (oC): -20 ~ 80

Rated Voltage (V):300

Professionally approved products. Datasheet

Construction:

Conductor: Bare Copper

Conductor Dia. (mm): 0.50 ± 0.02

Insulation: SR-PVC

Insulation Dia. (mm): 0.90 ± 0.10

A rip cord: 210 D

Jacket: PVC

Outer Dia. (mm): 4.8 ± 0.1

Colour:

The colour of the insulation: See Table

The jacket colour: White

Marking(3times/m):

RS 5202649 CW 1308 TELECOM 4PR

Professionally approved products. Datasheet

Mechanical Characteristics:

Test Object: Insulation

Test Material: PVC

Tensile Strength (Mpa): ≥ 12.5

Elongation (%): ≥ 125

Cold Bend (-20 +/- 2 °C x 4Hrs): No Crack

Heat Shock (80 +/- 2 °C x 2Hrs): No Crack

Electrical Characteristics:

Max.Conductor DC Resistance at 20°C (Ω /Km) :
<97.8

Min.Insulation DC Resistance at 20°C ($M\Omega \cdot KM$) :
>500

